

CUSBCHARKIT USB- Universalreiseladegerät im Set

Product Images



Short Description

- USB-Geräte (5V) dank hoher Ausgabe (max 2100 mA) aufladen
- Mobil- oder USB-Gerät ohne PC oder Notebook aufladen
- Kompaktes Design Inklusive Zubehörbeutel zum sicheren Transportieren von Gerät und Zubehör
- Ganzheitliche Schutzfunktionen: Kurzschlussschutz, Überlastungsschutz, Überspannungsschutz, Überhitzungsschutz
- Netzstecker kompatibel mit US, UK, AU und EU

Description

The Universal USB Travel Charger kit is an ideal solution for charging an iPad or tablet on the go, as well as most other devices that use a USB connection. Offering the versatility of charging directly from a power socket or from a 12V car cigarette port, the USB travel charger kit can handle voltages from 100 to 240 volt AC or 12 volt DC and converts them automatically to the 5 volt DC that USB devices use. As well as smart phones and tablets, the charger supports safe charging of many other devices such as navigation systems, MP3 players and digital cameras. Thanks to the high output power and 2 USB ports, the versatile Conceptronic Universal USB Travel Charger kit can charge 2 devices at the same time, and comes with built-in protection against over-charging and overheating. Perfect for travel or simply a busy lifestyle, the unit is compact and features a bag for keeping the included accessories safe. A must-have for the office, at home, in a car or when travelling.

Additional Information

Anzahl der Kartons pro Palette	16 piece
Volumen der Verpackung	2334.15 cubic_centimeter
Länge der Palette	800 millimeter
Breite der Palette	1200 millimeter
Höhe der Palette	1530 millimeter
Power Plug Type.	EU, UK, AU, US
Number of outputs.	2
USB Type-A ports quantity.	2
Programmable power supply (PPS) (YES/NO).	Nein
Material des Gehäuses	Polycarbonate (PC)
Number of simultaneously connected devices (max).	2
Port 1 Power Output.	DC 5.0V/1.0A
Port 2 Power Output.	DC 5.0V/2.1A
Code des Harmonisierten Systems (HS)	850440
Zolltariflicher Warencode (TARIC)	8504403090
Menge pro Palette	384 piece
Maximum AC Input.	240 volt
Minimum AC Input.	100 volt
Maximum power.	15.5 watt
Power Protection Features.	Over current, Over power, Short circuit
Einhaltung der Nachhaltigkeit	Nein
Operating temperature (T-T) Max.	40 celsius
Operating temperature (T-T) Min.	0 celsius
Storage relative humidity (H-H) Max.	90%
Storage relative humidity (H-H) Min.	10%

Operating relative humidity (H-H) Max.	80%
Operating relative humidity (H-H) Min.	20%
Storage temperature (T-T) Max.	80 celsius
Storage temperature (T-T) Min.	-20 celsius
Menge pro Packung	1 piece
Tiefe des Pakets	63 millimeter
Höhe des Pakets	190 millimeter
Breite des Pakets	195 millimeter
Gewicht der Verpackung	89 gram
Farbe	Weiß
EAN	4015867190531
Modellnummer	CUSBCHARKIT
Dimensions (W x D x H).	75 x 27 x 74 mm
Produkt Höhe	74 millimeter
Produkt Breite	75 millimeter
Produkt Tiefe	27 millimeter
Produkt Gewicht	201 gram
Produktgewicht (kg)	0,201
Inhalt des Pakets	Quick installation guide
Lieferumfang	CUSBCHARKIT Multilingual quick installation guide
Eingangsspannung	AC 100-240V 50/60Hz
Ausgangsspannung	5V/1A (Port 1), 5V/2.1A (Port 2)

