


FEP-1601W120, 16-Port Fast Ethernet PoE Switch, 802.3af/at PoE, 16-Port PoE Outputs, 120W Power Budget

Product Images



Short Description

- IEEE 802.3x Flow Control protects against lost packets for reliable data transmission
- 10/100Mbps, full/half-duplex, auto-negotiation, auto-MDI/MDIX
- PoE on/off control per port by dip switches
- 19-inch metal housing

Description

FEP-1601W120 is a 16-port 10/100Mbps Fast Ethernet Switch with Power over Ethernet (PoE) capability. With 16 dip switches, each PoE port can be manually set for On-Off control. FEP-1601W120 supports up to 30W on each LAN port when the DIP switch is in the ON position . Using a LevelOne PoE repeater, it is possible to extend the connection a

further 100 meters, or even daisy-chain several PoE repeaters together for greater distances. Dual 10/100Mbps ports can connect with other edge switches or NVR as uplink ports

Additional Information

802.3af/at PoE	16
Harmonized System (HS) code.	851762
Customs product code (TARIC).	8517620000
Grade.	Commercial
PoE Supported.	Yes
Manageable.	No
Fanless.	Yes
Concurrent ports.	Total 16.00
PoE Power Budget.	Total 120.00
Switching capacity.	3.2Gbps
Data Rate.	100Mbps
Power supply included.	Yes
Standard.	IEEE 802.3 10-BASE-T, Ethernet IEEE 802.3u 100-BASE-TX, Fast Ethernet IEEE 802.3x Full-duplex Flow ControlIEEE 802.3 10-BASE-T, Ethernet IEEE 802.3u 100-BASE-TX, Fast Ethernet IEEE 802.3x Full-duplex Flow ControlIEEE 802.3 10-BASE-T, Ethernet IEEE 802.3u 100-BASE-TX, Fast Ethernet IEEE 802.3x Full-duplex Flow ControlIEEE 802.3 10-BASE-T, Ethernet IEEE 802.3u 100-BASE-TX, Fast Ethernet IEEE 802.3x Full-duplex Flow ControlIEEE 802.3 10-BASE-T, Ethernet IEEE 802.3u 100-BASE-TX, Fast Ethernet IEEE 802.3x Full-duplex Flow ControlIEEE 802.3 10-BASE-T, Ethernet IEEE 802.3u 100-BASE-TX, Fast Ethernet IEEE 802.3x Full-duplex Flow ControlIEEE 802.3 10-BASE-T, Ethernet IEEE 802.3u 100-BASE-TX, Fast Ethernet IEEE 802.3x Full-duplex Flow ControlIEEE 802.3 10-BASE-T, Ethernet IEEE 802.3u 100-BASE-TX, Fast Ethernet IEEE 802.3x Full-duplex Flow ControlIEEE 802.3 10-BASE-T, Ethernet IEEE 802.3u 100-BASE-TX, Fast Ethernet IEEE 802.3x Full-duplex Flow Control
Mount.	19" rack mount
Flash memory size.	160
MAC address table.	4K
Indicators.	Power, Active, 10/100M, PoE

Backplane (Gbps).	3.2
Approval and Compliance.	FCC, CE, RoHS
Operating humidity.	10% RH ~ 90% RH
Operating temperature.	0°C ~ 45°C
Storage humidity.	10% RH ~ 90% RH
Storage temperature.	-40°C ~ 70°C
Package Contents.	FEP-1601W120, Power Cord, User Manual
Color.	Grey
EAN.	4015867199848
Model Number.	FEP-1601W120
Product weight (kg).	2,2
Dimensions (W x D x H).	480 x 118 x 44 mm

