

FGP-3400W760, 34-Port Fast Ethernet PoE Switch, 802.3at/af PoE, 32 PoE Outputs, 2 x Gigabit RJ45, 760W

Product Images



Short Description

- 32 Fast Ethernet PoE ports and 2 Gigabit ports
- IEEE 802.3af/at PoE compliant to simplify deployment and installation
- PoE on/off control per port by dip switches
- IEEE 802.3x Flow Control protects against lost packets for reliable data transmission
- 19-inch rackmount kit included

Description

The LevelOne FGP-3400 series are unmanaged PoE switches with 32 RJ45 PoE ports. The switches are IEEE 802.3af/at compliant, providing power and data over a single Ethernet cable to any PoE device, with a total power budget of 250/380/500/630/760W, or up to 30W per port. Ideal for desktops, they are also 19-inch rack-mountable, which provides convenient and flexible installation. The FGP-3400 switches are designed for small-to-medium businesses that require an affordable solution for deploying PoE infrastructure.

Additional Information

Gigabit RJ45/SFP combo	2
802.3af/at PoE	32
Harmonized System (HS) code.	851762
Customs product code (TARIC).	8517620000
Grade.	Commercial
PoE Supported.	Yes
Manageable.	No
Fanless.	No
Concurrent ports.	Total 34.00
PoE Power Budget.	Total 760.00
Switching capacity.	10.4Gbps
Product weight (kg).	3,1
Dimensions (W x D x H).	195 x 480 x 45 mm
Data Rate.	1Gbps, 100Mbps
Power supply included.	Yes
Heat dissipation.	FAN

Standard.	IEEE 802.3 10-BASE-T (Ethernet) IEEE 802.3u 100-BASE-TX (Fast Ethernet) IEEE 802.3ab 1000BASE-T (Gigabit Ethernet) IEEE 802.3x Flow Control (full-duplex flow control) IEEE 802.3af Power over Ethernet IEEE 802.3at Power over Ethernet PlusIEEE 802.3 10-BASE-T (Ethernet) IEEE 802.3u 100-BASE-TX (Fast Ethernet) IEEE 802.3ab 1000BASE-T (Gigabit Ethernet) IEEE 802.3x Flow Control (full-duplex flow control) IEEE 802.3af Power over Ethernet IEEE 802.3at Power over Ethernet PlusIEEE 802.3 10-BASE-T (Ethernet) IEEE 802.3u 100-BASE-TX (Fast Ethernet) IEEE 802.3ab 1000BASE-T (Gigabit Ethernet) IEEE 802.3x Flow Control (full-duplex flow control) IEEE 802.3af Power over Ethernet IEEE 802.3at Power over Ethernet PlusIEEE 802.3 10-BASE-T (Ethernet) IEEE 802.3u 100-BASE-TX (Fast Ethernet) IEEE 802.3ab 1000BASE-T (Gigabit Ethernet) IEEE 802.3x Flow Control (full-duplex flow control) IEEE 802.3af Power over Ethernet IEEE 802.3at Power over Ethernet PlusIEEE 802.3 10-BASE-T (Ethernet) IEEE 802.3u 100-BASE-TX (Fast Ethernet) IEEE 802.3ab 1000BASE-T (Gigabit Ethernet) IEEE 802.3x Flow Control (full-duplex flow control) IEEE 802.3af Power over Ethernet IEEE 802.3at Power over Ethernet PlusIEEE 802.3 10-BASE-T (Ethernet) IEEE 802.3u 100-BASE-TX (Fast Ethernet) IEEE 802.3ab 1000BASE-T (Gigabit Ethernet) IEEE 802.3x Flow Control (full-duplex flow control) IEEE 802.3af Power over Ethernet IEEE 802.3at Power over Ethernet Plus
Power Output.	Per Port 56VDC, Max. 30 watts
Mount.	19" rack mount
Flash memory size.	8Mbit
MAC address table.	32K
Jumbo frame (KB).	16
Indicators.	Power, Uplink, LAN 1~32 port, PoE 1~32 port
Backplane (Gbps).	10.4

Approval and Compliance.

FCC Class A, CE EMI: EN55032:2012+AC:2013
 EN55022:2010+AC:2011 AS/NZS CISPR 22 Amdt.
 (2010) EN61000-3-2:2014 EN61000-3-3:2013
 EMS: EN55024:2010 IEC61000-4-2:2008
 IEC61000-4-3:2006+A1:2007+A2:2010
 IEC61000-4-4:2012 IEC61000-4-5:2005
 IEC61000-4-6:2013 IEC61000-4-8:2009
 IEC61000-4-11:2004"FCC Class A, CE EMI:
 EN55032:2012+AC:2013 EN55022:2010+AC:2011
 AS/NZS CISPR 22 Amdt. (2010)
 EN61000-3-2:2014 EN61000-3-3:2013 EMS:
 EN55024:2010 IEC61000-4-2:2008
 IEC61000-4-3:2006+A1:2007+A2:2010
 IEC61000-4-4:2012 IEC61000-4-5:2005
 IEC61000-4-6:2013 IEC61000-4-8:2009
 IEC61000-4-11:2004"FCC Class A, CE EMI:
 EN55032:2012+AC:2013 EN55022:2010+AC:2011
 AS/NZS CISPR 22 Amdt. (2010)
 EN61000-3-2:2014 EN61000-3-3:2013 EMS:
 EN55024:2010 IEC61000-4-2:2008
 IEC61000-4-3:2006+A1:2007+A2:2010
 IEC61000-4-4:2012 IEC61000-4-5:2005
 IEC61000-4-6:2013 IEC61000-4-8:2009
 IEC61000-4-11:2004"FCC Class A, CE EMI:
 EN55032:2012+AC:2013 EN55022:2010+AC:2011
 AS/NZS CISPR 22 Amdt. (2010)
 EN61000-3-2:2014 EN61000-3-3:2013 EMS:
 EN55024:2010 IEC61000-4-2:2008
 IEC61000-4-3:2006+A1:2007+A2:2010
 IEC61000-4-4:2012 IEC61000-4-5:2005
 IEC61000-4-6:2013 IEC61000-4-8:2009
 IEC61000-4-11:2004"FCC Class A, CE EMI:
 EN55032:2012+AC:2013 EN55022:2010+AC:2011
 AS/NZS CISPR 22 Amdt. (2010)
 EN61000-3-2:2014 EN61000-3-3:2013 EMS:
 EN55024:2010 IEC61000-4-2:2008
 IEC61000-4-3:2006+A1:2007+A2:2010
 IEC61000-4-4:2012 IEC61000-4-5:2005
 IEC61000-4-6:2013 IEC61000-4-8:2009
 IEC61000-4-11:2004"

Operating humidity.	0% RH ~ 90% RH
Operating temperature.	0°C ~ 40°C
Storage humidity.	0% RH ~ 90% RH
Storage temperature.	-20°C ~ 70°C

Package Contents.	FGP-3400W250 Stromkabel Gummifüße Quick Installation Guide
Color.	Black
EAN.	4015867203286
Model Number.	FGP-3400W760

