

FCS-3054 HUBBLE Fixed Dome IP Network Camera, 3-Megapixel, 802.3af PoE, Vandalproof

Product Images



Short Description

- 3-Megapixel high-definition resolution
- Video compression: H.264, MJPEG
- Power support: PoE (IEEE 802.3af)
- Built-in Micro SDHC/SDXC card slot for local storage

Description

The LevelOne FCS-3054 is an indoor IP surveillance camera with clear, sharp images in 3 Megapixel resolution. The FCS-3054 is suitable for every imaginable interior surveillance. In addition, the camera supports PoE, enabling power and data transmission over a single Cat.5 cable, making installation fast and flexible. It mini dome housing make to

Suitable for more installation environments

Additional Information

Fast Ethernet RJ45	1 x RJ-45 10/100 Mbps PoE port
Harmonized System (HS) code.	852589
Customs product code (TARIC).	8525890000
Features.	Video: Image Setting: - Adjustable image size, quality and bit rate - Configurable brightness, sharpness, contrast, saturation, white balance and exposure - AGC/AWB/AES - Back Light Compensation (BLC) - 2D Noise Reduction (2DNR) Streaming: Up to 2 video streams
2-way audio.	No
DI/DO.	No
IR LED for night vision.	No
Max. Resolution.	3 Megapixels
IP Camera series.	HUBBLE
Camera Type.	Dome
Zoom type.	Fixed
PoE Supported.	Yes
Dimensions (W x D x H).	110 x 110 x 58 mm
Product weight (kg).	0.202
Angle of view (°).	83.3°
Image sensor.	3-Megapixel 1/3.2" Progressive Scan CMOS
Indicators.	Power
IR cut filter.	No
Lens.	Fixed focal, Fixed iris, Fixed focus, f2.93mm , F2.0
Minimum illumination (lux).	Color: 0.1 lux at F2.0
Mount.	Ceiling mount, Wall mount
Port Configuration.	RE-45 10/100 Mbps
Power consumption.	2.9W

3 9/26/25

Power supply included.	No
Resolution.	15 fps at 2048 x 1536; 30 fps at 1920 x 1080; 30 fps at 1280 x 720; 30 fps at 640 x 480; 15 fps at 320 x 24
Shutter time.	1/5 ~ 1/10,000 sec
Standard.	IEEE 802.3 10-BASE-T, Ethernet IEEE 802.3u 100-BASE-TX, Fast Ethernet IEEE 802.3af Power over Ethernet (PoE) IEEE 802.1X Network Access Control TCP, UDP, HTTP, HTTPS, DHCP, PPPoE, RTP, RTSP, IPv6, DNS, DDNS, NTP, ICMP, ARP, IGMP, SMTP, FTP, UPnP, SNMP, Bonjour
Supported storage capacity.	64 GB
Video format.	H.264 / MJPEG
Approval and Compliance.	EMI/EMS: CE, RoHS, FCC, IK08 Environmental Test: Vandal Resistant IK08-reted
Operating humidity.	10% RH ~ 85% RH
Operating temperature.	-10°C ~ 50°C
Supported browsers.	IE9 Above
Package Contents.	FCS-3054 Quick Installation Guide Ressource CD
Color.	White
EAN.	4015867189689
Model Number.	FCS-3054

