

USB-0401, Gigabit USB Network Adapter

Product Images



Short Description

- 10/100/1000Mbps wire speed transmission and reception
- Minimize carbon footprint with advanced energy efficient technology (IEEE 802.3az)
- 9K jumbo frames to increase data transfer rates
- Built-in Wake-on-LAN feature to startup computers remotely
- Supports IPv4/IPv6 network operation
- No additional power supply required
- Multi-platform support: Windows, Mac OS

Description

The LevelOne USB-0401 Gigabit USB Network Adapter allows you to connect to the internet easily through the built-in USB port on your laptop. This is an ideal solution for MacBook or other Windows computers that may have wireless built-in but don't come with an Ethernet port. Sometimes you need to physically connect to a network cable to help transfer files or access secure information. The USB-0401 easily does the job, all through your USB port.

The USB-0401 is USB 2.0 and 3.0 compliant. It also follows the Ethernet standards set by the IEEE 802.3/3u and 802.3ab, allowing you to take advantage of Gigabit Ethernet speeds of up to 1000Mbps. This provides a strong backbone for any high-speed broadband connection to the internet as well as fast speeds for the Local Area Network file transfers.

This makes the USB-0401 the best choice for reliability, efficiency and standard compliance.

Additional Information

Harmonized System (HS) code.	851762
Customs product code (TARIC).	8517620000
Color.	Black
EAN.	4015867225875
Model Number.	USB-0401
Host Interface.	USB-A
Network Card Type.	Wired
Dimensions (W x D x H).	23.4 x 16.5 x 51 mm
Product weight (kg).	0.025
Data Rate.	1Gbps
Indicators.	Link/Act
Jumbo frame (KB).	9
Power supply.	USB power
Standard.	● IEEE 802.3: 10Base-T (Ethernet) ● IEEE 802.3u: 100Base-TX (Fast Ethernet) ● IEEE 802.3ab: 1000Base-T (Gigabit Ethernet) ● IEEE 802.3x Flow Control (full-duplex flow control) ● IEEE 802.3az-2010 Energy Efficient Ethernet ● IEEE 802.1P layer 2 Priority Encoding and Decoding ● IEEE 802.1Q VLAN tagging
Approval and Compliance.	● CE ● RoHS
Operating temperature.	0°C ~ 70°C
Compatible operating systems.	● Windows XP/Vista/7/8/10 ● macOS X 10.9/10/11/12/13/14/15 ● macOS Big Sur 11.3 ● macOS Monterey 12.0.1/12.6.3
Package Contents.	USB-0401 Quick Installation Guide

